

东莞市国亚电子有限公司 DONGGUO GUOYA ELECTRONICS CO.,LTD

地址:广东省东莞市长安镇增田村横增路 72 号

Address:72 Hengzeng Road, Zengtian Village, Chang' an Town, Dongguan cigy, Guangdong Province

E-Tel:0769-81769816 传真: 0769-87089563 E-mail:gya1688@gdgya.com

网址: https://shop1415292614015.1688.com

Type Document	Crimp Specification	Α	
Date Issued:		Data Revised:	2014/11/02
Subject: A1254T-XXX	Issued By:		
1.25mm Pit	Engineering Dept.		

Description:

Height and width of crimped core should he set as required.

(Crimped height and width of wire barrel)


According to the external diameter and the type of electric wire, the width of crimped sheath shall be adjusted


wire won't be easily taken off from contact nor too much crimped.

(Crimped width of insulation barrel)

Position Graph:

QQ:316563782 贸易通: dachan88





Note:

- 1. Conductor crimp width. W1
- 2. Conductor crimp height. H2
- 3. Insulator crimp width. W1
- 4. Insulator crimp height. W2
- 5. Conductor wire shall be dimension long (mm) out A.
- 6. Naked part of sheathed wire must be located in the vicinity of center B.
- 7. The Crimp mouth must be equipped like Shell.



东莞市国亚电子有限公司 DONGGUO GUOYA ELECTRONICS CO., LTD

地址: 广东省东莞市长安镇增田村横增路 72 号

Address:72 Hengzeng Road, Zengtian Village, Chang' an Town, Dongguan cigy, Guangdong Province

E-Tel:0769-81769816 传真: 0769-87089563 E-mail:gya1688@gdgya.com

网址: https://shop1415292614015.1688.com

Type Document	Crimp Specification	Revised /Edition	Α
Date Issued:		Data Revised:	2014/11/02
Subject: A1254T-XXX	Issued By:		
1.25mm Pit	Engineering Dept.		

Requirement:

QQ:316563782 贸易通: dachan88

Subject: UL 1571 or equivalent type electric wire									
AWG#	Conductor (mm ²)		Insulation Diameter		Insulator skins length		Dim. L (mm) out		
#32~#28	0.09~0.04mm ³	0.09~0.04mm²		0.90~0.65mm		1.0~1.5mm	0.4~0.6mm		
Wire Gauge	Conductor Crimp Area		Insulator Crimp Area		Terminal Tensile				
(AWG#)	Width(W1)	Height(H1)		Width(W2)		Height(H2)	Strength		
#28	0.50		0~ 0 .55mm			0.90~1.00mm	1.0Kgf		
#30	0.80~0.90mm 0.	0.4	5~ 0 .50mm	1.00mm	Max	0.80~0.90mm	0.5Kgf		
#32		0.4	0~0.45mm			0.70~0.80mm	0.3Kgf		

Remarks:

Unalike equipments and crimp reel molds skill facility or not shall be difference to result in dissimilar.

Signature: ______ ENG

Dong Guan Guo Ya Connectors co., ltd.